

Model	NVR1W08	
System	Main processor	Hi3536D
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	8-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/9/16
Video	Video input (IP)	8*5M@15fps/4*5M/8*1080P
	Access bandwidth	64Mbps
	Forwarding bandwidth	64Mbps
	Video compression	H.265+/H.265+/H.265/H.264
	Display quality	Max 1920*1080
	Playback quality	5M/1080P
	Decode	1*5M/2*1080P
	VR	Unsupport
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	Unsupport
record &play back	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local payback	1*5M/2*1080P
	Search mode	Search by Time/Calendar/Event/Channel
	Record storage	HDD、 Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI HD output
	Audio I/O	0/0
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port
	USB interface	2*USB2.0 ports
	HDD	1*SATA(Up to 8TB for each disk)
	ESATA	No
	Serial interface	No
Other	ONVIF	Support
	Power supply	12V/2A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0°C- + 55°C , Humidity:10% - 90%RH , Atm:86kpa - 106kp
	Dimension	260*43*190MM
	Weight	A total of about 2kg