

3S SMART SECURITY SYSTEM

HD-IP IR SPEED DOME: PTIPVM18XS200FC Starlight full color

- * Standard ONVIF ;
- * Support P2P function
- * 4.5" half metal body construction, IP66
- * 4pcs Array 42Mil Led + 4pcs laser LED, Support warm light, IR range up to 100M
- * Compatible with HIKVISION, DAHUA, XM, Video park NVR .etc
- * Compatible with CMS,UC2, Milestone, NUUO and AXXON platform.etc
- * Intelligent IR illumination & power consumption is variable, dependant the zoom factor



Specification	
Camera	
Solution	HI3516E+IMX307
Sensor	1/2.7" CMOS 2MP IMX307
Output Pixel	1920x1080
Lens	18X f=5.35mm~96.3mm
BLC	Support
AGC	Auto/Manual
WB	Indoor/Outdoor/Auto/Manual
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Software Control	IE, UC2, Management Platform, P2P
Mobile View(optional)	Android , iPhone
Rotation range	Pan:0~360°,Tilt:0~93°
Rotation speed	Pan:0-45°/s Tilt:0-30°/s
Auto Flip	Horizontal 180°,Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmable(scan speed 1-64 levels setting available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
video compression	H.264/H.265M-JPEG
audio compression	G711~PCM
Operating temperature	-40°C~+60°C
Operation menu	English
Power	DC 12V 4A
Consumption	≤25W
Lightning Protection	Transient voltage 6000V
Related validation	IP66,CE,FCC,RoHS
IR parameters	
Auto Control IR LED	PWM
LEDs	4pcs Array 42Mil Led + 4pcs laser LED
IR distance	Up to 100 meters
Support ambient light detection	IR illumination on 1-9 grades selectable

