

TELEtek®



MV-1008

- Active/passive Terrestrial switch
- LED indicators at taps
- Terminal/cascade switch
- Compact design
- A class, CE approved
- DiSEqC 2.0 compatible
- External SMPS power supply

Product Features

Model		MV-1008	MV-1012	MV-1016	MV-1020	MV-1024	MV-1032
Inputs	SAT polarities + Terr	9IF+1Terr					
Tap Number		8	12	16	20	24	32
Trunk Loss (dB)	SAT 950...2150MHz	-1...-2,5	-1...-5		-2...-5		-2...-7
Tap Loss (dB)		-2....+2	-2...0		-3...0		-3...-1
Trunk Loss (dB)	Terr 47...862MHz	-2...-3					-2,5...-3,5
Tap Loss (dB) Passive	Terr 5...862MHz	-38...-28	-40...-33		-42...-35		-43...-38
Isolation	H/V	>30dB					
Return Loss	Terr 47...862MHz	>10dB					
	SAT 950...2150MHz						
Output level	SAT (IMD3, EN50083-5)	100 dBμV					
	Terr (IMD3, EN50083-5)	92 dBμV					
LNB Power Supply		12Vdc / 1500 mA					
Consumption From The Receiver		40 mA					
Switching commands		DiSEqC 2.0 / 13V, 18V, 13V+22KHz, 18V+22KHz					
Dimensions LxWxH (cm)		11x13x4	17x19x4		23x19x4		30x19x4

TELEtek Elektronik San.Tic.A.Ş.

Merkez Mah. Ayazma Cad. Demet İş Merkezi No:55 Kat:1 34406
Kağıthane İstanbul TÜRKİYE

☎ +90 212 295 97 00
☎ +90 212 295 42 43
✉ teletek@teletek.com.tr

Türkiye
Discover
the potential



