

TELEtek®



MV-1720

- Active/passive Terrestrial switch
- 12V 0,15A Terrestrial feeding
- LED indicators at taps
- Terminal/cascade switch
- Compact design
- A class, CE approved
- DiSEqC 2.0 compatible
- External SMPS power supply

Product Features

Models		MV-1708	MV-1712	MV-1716	MV-1720	MV-1724	MV-1732
Inputs	SAT polarities + Terr	16IF+1Terr					
Tap Number		8	12	16	20	24	32
Trunk Loss (dB)	SAT 950...2150MHz	-1...-3	-1...-5		-2...-5		-2...-7
Tap Loss (dB)		-4...-2	-5...-3		-6...-3		-6...-4
Trunk Loss (dB)	Terr 47...862MHz	-2...-3					-2,5...-3,5
Tap Loss (dB) Active		-27...-5	-19...-8		-21...-11		-21...-12
Tap Loss (dB) Passive	Terr 5...862MHz	-38...-26	-40...-29		-42...-32		-43...-33
Isolation	H/V	>30dB					
Return Loss	Terr 47...862MHz	>10dB					
	SAT 950...2150MHz						
Output level	SAT (IMD3, EN50083-5)	100 dB _μ v					
	Terr (IMD3, EN50083-5)	92 dB _μ v					
Consumption From The Power Supply	@12V Power Supply	12 Vdc / 4000 mA					
Consumption From The Receiver		40 mA					
Switching commands		DiSEqC 2.0 / 13V, 18V, 13V+22KHz, 18V+22KHz					
Dimensions LxWXH (cm)		12x31x4	19x31x4		26x31x4		31x31x4

TELEtek Elektronik San.Tic.A.Ş.

Merkez Mah. Ayazma Cad. Demet İş Merkezi No:55 Kat:1 34406
Kağıthane İstanbul TÜRKİYE

+90 212 295 97 00

+90 212 295 42 43

teletek@teletek.com.tr

Türkiye
Discover
the potential

