

TELEtek®



MY-920

- Equalisation of cable loss by constant 8dB slope gain
- Feeding by trunkline only
- Low noise figure

Product Features

Model		MY-930	MY-921	MY-920
Inputs and outputs	SAT polarities+Terr	9IF+1Terr		
Gain (dB)	SAT 950...2150MHz	22...29	14...20	12...20
	active Terr 47...862MHz	19...20	19...20	-
	passive Terr 5...862MHz	-1...-2	-1...-2	0...-1
Gain adjustment (dB)	SAT 950...2150MHz	20	20	-
	Terr 5...862MHz			
Output power (dBμV)	SAT (IMD3, EN50083-5)	112	112	105
	active Terr (IMD3, EN50083-5)	110	110	-
	passive Terr (IMD3, EN50083-5)	-	-	-
Return loss (dB)	SAT 950...2150MHz	>10	>10	> 10
	active Terr 47...862MHz			-
	passive Terr 5...862MHz			> 14
Operating voltage (V)		13		
Current consumption (A)		1,4	0,8	0,25
Current pass (All SAT ports DC pass) (A)				
Dimensions	LxWxH (cm)	17x11,5x4		

TELEtek Elektronik San.Tic.A.Ş.

Merkez Mah. Ayazma Cad. Demet İş Merkezi No:55 Kat:1 34406

Kağıthane İstanbul TÜRKİYE

☎ +90 212 295 97 00

✉ +90 212 295 42 43

✉ teletek@teletek.com.tr

Türkiye
Discover
the potential

