



TK-1308



- Active/passive Terrestrial switch
- 12V 0,15A Terrestrial feeding
- LED indicators at taps
- Compact design
- A class, CE approved
- DiSEqC 2.0 compatible
- External SMPS power supply

Product Features

Models		TK-1308	TK-1312	TK-1316	TK-1320	TK-1324	TK-1332	TK-1350
Inputs	SAT polarities + Terr	12IF+1Terr						
Tap Number		8	12	16	20	24	32	50
Trunk Loss (dB)	SAT 950...2150MHz	-1...-2	-2...-4		-2...-5		-2...-6	-3...-11
Tap Loss (dB)		-1...+2	-2...+1		-2...0		-2...-1	-8...-5
Trunk Loss (dB)	Terr 47...862MHz	-4...-5						
Tap Loss (dB) Active		-4...-1	-4...-2		-4...-3		-5...-4	-18...-9
Tap Loss (dB) Passive	Terr 5...862MHz	-24...-21	-24...-22		-24...-23		-25...-24	-38...-29
Isolation	Terr to SAT	>24dB						
	SAT to Terr	>30dB						
	Cross polar. H/V	>35dB						
Isolation Between Users	Terr to Terr	>30dB						
	Sat to Sat							
Return Loss	Terr 47...862MHz	>10dB						
	SAT 950...2150MHz							
Output level	SAT (IMD3, EN50083-5)	100 dBμV						
	Terr (IMD3, EN50083-5)	92 dBμV						
LNB Power Supply		12 Vdc / 4000 mA						
Consumption From The Receiver		50 mA						
Switching commands		DiSEqC 2.0 / 13V, 18V, 13V+22KHz, 18V+22KHz						

Dimensions LxWxH (cm)	12x31x4	19x31x4	26x31x4	31x31x4	47,5x31x4
-----------------------	---------	---------	---------	---------	-----------

TELEtek Elektronik San.Tic.A.Ş.

Merkez Mah. Ayazma Cad. Demet İş Merkezi No:55 Kat:1 34406

Kağıthane İstanbul TÜRKİYE

+90 212 295 97 00

+90 212 295 42 43

teletek@teletek.com.tr

Türkiye
Discover
the potential

